



**1. INTRODUCTION**

A silicone based foaming dressing designed to provide a convenient and efficient method of cleaning and protecting tyres.

SAS43 – 500ml Aerosol

**2. WHERE TO USE**

On all automobile, commercial and heavy truck tyres.

**3. WHERE NOT TO USE**

- On tyre treads. This product is designed for sidewall use only.

**4. BENEFITS**

- High silicone content.
- Protection against surface cracking.
- Triple action, cleans, shines, protects.
- Ease of use. Spray and leave. No post-application measures necessary.
- Restores original appearance.

**5. PHYSICAL PROPERTIES (Base dressing except where stated).**

Appearance	A milky white emulsion.
pH	1.0 +/- 1.0
Specific Gravity	0.990 +/- 0.01
Non Volatiles % m/m	20 – 30
Active Content % m/m, as supplied	20 – 30
Viscosity @ 20 C	Thin mobile liquid
Flammability, as supplied	Extremely flammable, flash point below -20 C.
Composition Data, as supplied	A silicone resin emulsion containing a corrosion inhibition package in butane/isobutene/propane propellant.
Service Temperature (Continuous)	Designed for use at ambient temperatures.

**6. APPLICATION DETAILS**

For optimum results, apply to pre-cleaned tyre walls.

Shake can before use. Apply to tyre walls. Allow foam to develop and subsequently collapse, leaving a streak free finish with a high sheen. Remove any overspray with a damp cloth.