



1. INTRODUCTION

A dry aerosol spray designed to physically remove superficial dirt, grime and other loosely adhering contaminants where “wet” or other normal chemical products are not permissible.

SAS54 – 500ml Aerosol

2. WHERE TO USE

- On all types of isolated electrical components and other area of difficult accessibility.

3. WHERE NOT TO USE

- Near unprotected skin.
- Live electrical equipment.

4. BENEFITS

- High pressure discharge.
- Accurate and precise application with the integral extension tube.
- Instantaneous action.
- Immediate evaporation.
- Can be used inverted as a freezer spray/chewing gum remover.

5. PHYSICAL PROPERTIES (Duster base except where stated).

Appearance	Clear colourless highly volatile liquefied gas.
pH (10% solution)	Not applicable
Specific Gravity	0.533 @ 20 C (Nominal)
Viscosity	Not applicable
Non Volatiles % m/m	100
Active Content % m/m, as supplied	100
Flammability, as supplied	Extremely flammable
Composition Data, as supplied	Butane, iso-butane and propane blend.
Service Temperature (Continuous)	Designed for use at ambient temperatures.

6. APPLICATION DETAILS

Ensure electrical equipment is isolated and static has been discharged. Spray directly to the area. Keep can upright whilst using, failure to do so may result in liquid discharge and freezing effect.

CAUTION: This product consists of a liquefied gas. Liquid splashes may cause freeze burns to skin and eyes. Always read the Safety Data Sheet before use.