



1. INTRODUCTION

A silicone free dressing designed primarily for the maintenance of rubber parts and components.

SAS57 – 500ml Aerosol

2. WHERE TO USE

- Rubber seals on doors, bonnets, tailgates, tyre walls etc... can also be used as a general purpose release agent on moulding tools.

3. WHERE NOT TO USE

- No major restrictions.

4. BENEFITS

- Silicone free – safe for use in body shops.
- Helps prevent cracking and eliminates rubber squeal.
- Excellent release properties.
- Very low odour.
- Excellent surface slip.
- Excellent flow properties.

5. PHYSICAL PROPERTIES (Base except where stated).

Appearance	A colourless to pale yellow oily liquid.
pH	Not applicable
Specific Gravity	0.77 – 0.79
Viscosity	Thin free flowing liquid.
Non Volatiles % m/m	40 – 50
Active Content % m/m, as supplied	5 – 15
Flammability, as supplied	Extremely flammable, flash point below -20 C
Composition Data, as supplied	A solution of vegetable oils in naphtha (petroleum) hydrotreated light, in butane, isobutene and propane propellants.
Service Temperature (Continuous)	Up to 180 C
Service Temperature (Intermittent)	Up to 200 C

6. APPLICATION DETAILS

Shake can thoroughly before use. Spray directly onto the component, from a distance of 20 – 30cm, ensuring even coverage.