



1. INTRODUCTION

A highly effective blend of detergents and sequestrates ideal for the removal of traffic film from vehicle bodies. Can also be used for general degreasing and cleaning.

SAS1040

2. WHERE TO USE

- On all exterior surfaces of vehicles.

3. WHERE NOT TO USE

- On painted surfaces without rinsing.
- On materials sensitive to alkali liquids.

4. BENEFITS

- Economical in use
- Removes traffic film
- Removes oil and grease
- Dilution up to 1:65
- Low odour

5. PHYSICAL PROPERTIES

Appearance	Clear, pale straw coloured liquid
pH	10 to 12
Specific Gravity	1.030 +/- 0.015
Composition Data, descriptive	An aqueous solution of sodium hydroxide, detergents and sequestrates.
Viscosity	Low viscosity
Non Volatiles %m/m	9.0 +/- 1.0
Application Temperature	5 – 7 °C (diluted through a pressure washer)

6. APPLICATION DETAILS

Pressure Washers: Adjust the detergent feed according to the level of soiling of the surface to be cleaned. Rinse off thoroughly with water

Low Pressure Spray: Apply diluted solution and allow 2 – 5 minutes contact time. Rinse off thoroughly with hot or cold water.

Typical Dilution	Machine	By Hand	Low Pressure Spray
Traffic Film Removal	1:33 / 1:65	1:50	1:5
Engine Degreasing	1:10 / 1:25	1:20	1:3
Chassis Cleaning	1:20 / 1:35	1:25	1:3
Dilution will be affected by the type and degree of soiling and local water hardness			

CAUTION: Product must always be tested on alkali sensitive surfaces before use. Never use this product in direct sunlight or allow the product to dry out on the surface or staining may result.