



1. INTRODUCTION

A premium quality emulsion based upon silicone and carnauba wax.

SAS1046

2. WHERE TO USE

- This product is design primarily for use on automotive finishes but can also be used for exterior use on caravans and camper vans where a high gloss, sealed finish is required.
- It is compatible with most hard substrates including coated and painted steels, aluminium and other reflective metals, including chromium plating and most plastics including glass reinforced polyester.

3. WHERE NOT TO USE

- On any area where increased slip would create hazards, e.g. flooring, steering wheels, foot pedals etc.
- On glass or clear plastics where smearing may occur.
- On surfaces likely to be painted.
- On hot surfaces, or in strong direct sunlight.

4. BENEFITS

- Seals micro cracks against ingress of rain and environmental contaminants.
- Ease of application and economy in use.
- Based upon a silicone rich system for enhanced gloss and water resistance.
- Contains a soft abrasive to gently remove superficial staining and help restoration of aged finishes.
- Resistant to detergent wash off.

5. PHYSICAL PROPERTIES

Appearance	Viscous yellow paste
pH	Not applicable
Specific Gravity	1.015 to 1.035
Composition Data, descriptive	An aqueous emulsion containing silicone fluids, wax, non-ionic surfactants, emulsifiers, thixotropes and a sift abrasive in a blend of hydrocarbon solvents.
Non Volatiles %m/m	15 to 25
Viscosity	4000 to 6000 cPs
Flammability, as supplied	Non flammable, wholly water based
Application Temperature	Ambient temperatures

6. APPLICATION DETAILS

Apply to clean dry paintwork.

Shake container thoroughly before use. Ensure suitability for use by applying to a small inconspicuous test area prior to full application.

Pour onto a soft, dry, lint free cloth and apply sparingly and evenly to one panel at a time using a circular motion.

Allow to dry to a light haze and buff with a soft, dry lint free cloth.