



1. **INTRODUCTION**

A highly effective blend of detergents and sequestrates ideal for general degreasing and cleaning.

SAS1059

2. **WHERE TO USE**

- On metal, plastic or painted surfaces.

3. **WHERE NOT TO USE**

- On metal or painted surfaces without rinsing.
- On materials sensitive to alkali liquids

4. **BENEFITS**

- Removes oil and grease
- Economical, dilutable up to 1:30
- Low Odour
- Water based.

5. **PHYSICAL PROPERTIES**

Appearance	Clear, pale straw coloured liquid
pH	12 to 14
Specific Gravity	1.055 +/- 0.015
Composition Data, descriptive	An aqueous solution of sodium hydroxide, deyergets and sequestrates.
Non Volatiles %m/m	18 +/- 1.0
Viscosity	Low viscosity
Flammability, as supplied	Non flammable
Application Temperature	5 to 70°C (diluted through a pressure washer)

6. **APPLICATION DETAILS**

Pressure Washer: Adjust the detergent feed according to the level of soiling of the surface to be cleaned. Rinse off thoroughly with water.

Low Pressure Spray: Apply diluted solution and allow 2 -5 minute contact time. Rinse thoroughly with hot or cold water.

Typical Dilution	Machine	By Hand	Low Pressure Spray
Traffic Film Remover	1:65 / 1:130	1:100	1:10
Engine Degreasing	1:25 / 1:50	1:40	1:5
Chassis Cleaning	1:40 / 1:65	1:50	1:5

NB: Dilutions will be effected by the type and degree of soiling and local water hardness.

Caution: Product must always be tested on alkali sensitive surfaces before use. Never use this product in direct sunlight or allow the product to dry out on the surface or staining may result.