



Salmon Fields, Royton, Oldham, OL2 6HZ, England.
Tel: 0161 627 0101 Fax: 0161 627 0971.
web: www.jamesbriggs.co.uk

PRODUCT INFORMATION SHEET

FOOD SAFE LUBRICANT

Reference FSFSL 16P; Amendment 0, September 2007

1 Introduction

Food Safe Lubricant is a general purpose silicone free, high tack, very high viscosity grease-like lubricant, based upon FDA listed components, and NSF registered to Category H1 [General – Incidental contact].

2. Where to Use

All normal food processing applications including meat plants, dairies, bakeries, canneries, bottling plants, etc. Food Safe Lubricant is suitable for use on all types of linkages, roller pins, sprockets, slides, guide rails, castors and gears etc. This product is also suitable for use on food related equipment including tail lifts, fork lift trucks, and curtain sides.

3. Where not to use

- On non metallic surfaces.

4. Benefits

- NSF Registration Number 131543
- Formulated to comply with FDA, Title 21, Section 178.3570
- Based upon vegetable derived lubricants
- Temperature range -10 to 150 °C (Grease melt Point 45 °C)
- Free of animal derivatives
- Outstanding lubrication
- Non slumping
- Resists and prevents corrosion
- Good load bearing capabilities
- Extends component lives
- Provides anti-static properties
- Provides good release [anti-stick] properties

5. Physical Properties

Appearance	An opaque pale straw aerosol spray
pH	Not applicable
Specific Gravity [Base]	0.88 +/- 0.1 @ 20°C
Non Volatiles % m/m	70 - 80
Active Content % m/m	75 - 85
Consistency [Dried Base]	Viscous tacky grease
Flammability	Extremely flammable, flash point below -20°C.
Composition Data	A solution of a vegetable based lubricant, and hydrocarbon wax in an aliphatic solvent, and a hydrocarbon propellant.

6. Application Details

Shake can before use. Hold upright, and spray from a distance of 15 to 30cm.

7. Availability

400 ml. aerosols

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.