

## DESCRIPTION

A solvent-based semi-gloss coating which is resistant to mild chemicals, water, oil and grease. Suitable for use on concrete, steel and wooden floors in light to medium traffic areas.

## RECOMMENDED USES



For light to medium traffic areas.

## SPECIAL PROPERTIES

Resistant to mild chemicals, water, oil and grease spillage.

## COLOUR RANGE

Black; Clear; Dark Green (14C39); Dark Grey (18B25); Morning Mist (10A03); Princess Grey (00A05); Sherwood Green; Safety Yellow (08E51); Safety Red (04E53); Safety Blue (18E53); Tile Red; White.

## FINISH

Semi-gloss.

## VOLUME SOLID

48%

## COVERAGE



Johnstone's Flortred will cover at the rate of approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 2-4 hours.  
Recoat after 16-24 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

TC2 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25-50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.  
EU limit value for this product (Cat A/i): 600g/l (2007) / 500g/l (2010).  
This product contains max 450g/l VOC.

## FILM THICKNESS

Wet: 90µm, dry: 44µm.

## SIZE

Size: 2.5 Litre and 5 Litre. Note, some colours are only available in 5 Litre.

## PREPARATION

All surfaces to be painted should be clean, dry and free from dust, laitance and loose or flaking material. New concrete or cement should be allowed to mature for several months before painting. Very dense smooth concrete surfaces, such as power floated concrete, normally need to be acid etched before painting in order to promote satisfactory adhesion.

## APPLICATION



Stir well before use. Apply by brush or roller which should be fully loaded for best results. Apply evenly and avoid overspreading. First coat can be thinned up to 5% by volume of TC2 Thinner & Cleaner. Allow to dry overnight before applying a second coat if required. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with TC2 Thinner and Cleaner. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT.
- FLAMMABLE.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

