



USERS INFORMATION FOR WELDING GOGGLE TYPE WG-225, WG-207, WG-209, WG-235

AUTION

This welding goggle does not provide unlimited eye protection. For your own protection read these instructions completely before using this eye-protection.

REQUIREMENTS

This welding goggle complies with the requirements of the European Directive 89/686/CEE annex II by means of the European Standard EN166:1995 for WG-225/WG-207/WG-209, EN166:2001 for WG-235 "Personal Eye-protectors-Specifications" And pr EN175:1996 for WG-225/WG-207/WG-209, EN175:1997 for WG-235 "Equipment for eye and face protection during welding and allied processes".

MATERIAL DECLARATION

No parts of the eye-protector which are in contact with the wearer are made of materials which are known to cause any skin irritation.

STORAGE

When not in use, it is recommended to store the welding goggle in a clean and dry polybag or case for optimal protection.

DIRECTION FOR USE

This goggle has been designed for your personal safety. It must be worn for the whole duration of exposure to hazards, leave the work area if dizziness of irritation occurs, or if the goggle becomes damaged.

CLEANING AND MAINTENANCE


To maintain your goggle in good condition:

1. Do not use abrasive materials, clean and rinse in warm soapy water and dry with a soft cloth.
2. Any part of eye-protector which are in contact with the wearer shall be disinfected by alcohol.


FIELD OF USE

This welding goggle is designed to protect the user against eye injuries through mechanical impact. The goggle is marked on the ocular and the frame with a series of numbers and symbols to indicate the manufacturer, the field of use, the protection capabilities and performance characteristics of the eye-protector. The marking of the oculars and of the frame are signified as follows:

- Cover Lens ref 450°C-0000 (dimension Ø50mm x 1.8mm) 421C-0001(dimension:2"x4/4"x1.8mm)




- Protective lens ref 451°C-0000 (dimension Ø50mm x 2mm)



- Filters

The used filters must be EC certified and their dimension must be Ø50mm. 2"x4/4" The scale number must be adapted to the relevant welding process. To know their characteristics of protection, consult the marking and the notice of use the filters.

- Frame



REPLACEMENT OF SPARE PARTS, ACCESSORIES AND INSTRUCTIONS FOR FITTING

Only use original spare parts. To replace the lens, you should ensure the compatibility of marking and the right lens is fitted.

DURATION OF USE

Inspect for damage regularly. When the frame has become hard and brittle, the welding goggle should be replaced.

WARNING

- The product is for eye protection against moderate impact hazards but NOT unbreakable.
- Do not modify or alter the eye protector.
- Pitted or scratched lens reduce vision and seriously reduce protection and should be immediately replace.
- Always check with supervisory personnel to ensure you are being given the proper protection relative to working conditions, consult related European standards.
- Use only EC-certified oculars.
- The materials which may come into contact with the wearer's skin could cause allergic reactions to susceptible individuals.
- If the symbols F, B and A are not common to both ocular and the frame then it is the lower level which shall be assigned to the complete eye-protector.
- Toughened mineral filter oculars shall only be used in conjunction with a suitable backing ocular.

CERTIFICATION

CE mark was issued by the notified body 0070.

INSTITUTE NATIONAL DE RECHERCHÉ ET DE SECURITE
AVENUE DE BOURGOGNE / B. P. 27, F54501 VANDOEUVRE, FRANCE

AUTHORISED REPRESENTATIVE

GALIJU SARL