



1. INTRODUCTION

A multi purpose product with lubricating, cleaning, dewatering, penetrating and corrosion inhibition properties.

SAS20 - 500 ml Aerosol with 360 Valve
SAS6 - 200 ml Aerosol

2. WHERE TO USE

Virtually limitless application areas.

On all metallic surfaces and components including chains, cables, gears, tools, locks etc.

3. WHERE NOT TO USE

On plastics where stress cracking or softening may occur.

4. BENEFITS

- Long lasting lubrication.
- Moisture displacement.
- Moisture repellency.
- Formation of a temporary anti-corrosive coating.
- Ability to penetrate rust and corrosion deposits.
- Enhanced operating temperature range.
- Contains PTFE for improved lubricity and load bearing resistance.

5. PHYSICAL PROPERTIES

Appearance	A turbid pale straw liquid with a pleasant odour.
pH	Not applicable
Specific Gravity [base]	0.795 – 0.81
Non Volatiles % m/m	20-30
Viscosity	Thin liquid
Flammability, as supplied	Extremely flammable, flash point below -20°C.
Composition Data, as supplied	A solution of naphthenic oil, modified grease, water displacing additives and wetting agents, and PTFE in naphtha [petroleum], hydrocarbon heavy, in butane/isobutane/propane propellant.
Service Temperature [Continuous]	Up to 80°C
Service temperature [Intermittent]	Up to 150°C

6. APPLICATION DETAILS

Shake thoroughly before use. Spray directly onto the component or surface, from a distance of 15 to 25cm, and allow to penetrate or form a film.