

Technical Data Sheet

Product Name	Rema Tip Top Tyre Sealant
Product Code	TY303
Date	08/09/16
Supplier's name and address	Van-Line Ltd, Gelderd Road, Leeds LS12 6NA

Preventative all-purpose sealant for tube and tubeless tyres of all sizes.



Applied with a pump through the valve, REMA TIP TOP Tyre Sealant seals damages up to 6mm. For vehicles e.g. in agriculture, construction, ATV, industrial, lawn & garden & forestry tyres (please refer to local legal regulations, do not use in road vehicles like passenger cars or trucks).

REMA TIP TOP Tyre Sealant seals 2x more punctures than competition and offers 7x more corrosion resistance, while they last for the lifetime of the tyre. Thus, the user benefits from reduced downtime and tyre wear, enjoying lower operating costs associated with tyre air loss.

REMA TIP TOP Tyre Sealant contains a high proportion of synthetic fibers and rubber particulates in uniform suspension as a fluid carrier. When a puncture in the tread area occurs, the escaping air forces the carrier and fibers to the penetration making a solid permanent seal from the inside-out. Also for sealing bead leakage and slow porosity leaks.

Specially designed to prevent wheel/rim corrosion by using a combination of inhibitors that have been proven to be effective in protecting various metals from rust and corrosion.

Product can stay in the tyre indefinitely, helping to prevent against tyre and tube rot.

Proven, homogenous formula, glycol free; prevents corrosion of wheel and conditions the tyre inner liner. Freeze point: -23°C

Water soluble for easy clean up, non-toxic, not-flammable, freeze/ thaw stable, non-combustible bio-degradable; PH-value 10 -11; Color: black.