



## FACT SHEET

<b>Product Name</b>	<b>SAS Hydrophobic Paint Guard</b>
<b>Product Code</b>	SAS2021
<b>Date</b>	25/05/16
<b>Supplier's name and address</b>	SAS Attack, Gelderd Road, Leeds LS12 6NA

SAS Hydrophobic Paint Guard is an easy on easy off sealant for those who want nothing but the best protection, durability, shine and beading. SAS Hydrophobic Paint Guard offers a hydrophobic guard and will help protect your car's paint from bird droppings, acid rain, bugs, road salts and other elements. For extended results SAS Hydrophobic Paint Guard can be layered with a 8 hours gap between applications.

### How to use

Apply in a cool shaded area, lightly wet either a cotton make up pad or a microfibre applicator pad with the SAS Hydrophobic Paint Guard coating and begin wiping it in evenly, using light pressure and overlapping strokes. Once on, leave the SAS Hydrophobic Paint Guard to dry for a minimum of 5 minutes and then buff off the residue using a microfibre towel.

### SAS Hydrophobic Paint Guard Spray 1ltr Spray

Add 25ml of SAS Hydrophobic Paint Guard to a 1ltr spray bottle and fill the remaining with 975ml of clean water (ideally RO water). Wash your car in the normal way, allow to drip dry for a few minutes, spray the mixed solution all over the car, coating the paintwork, glass, plastics, alloys, steel and rubbers, dry your car in the normal way following the top up application.

We hereby confirm that the above product meets all the required manufacturing specifications and Quality Control procedures as implemented by SAS Attack.