

GP Batteries

Product Specification

Model No.: GPPB19BS

Product Name : GP PowerBank Universal
 Description : Universal battery charger with external adaptor
 Input Voltage : 240V AC 50Hz
 Output Voltage : D/C/AA/AAA 2 x 2.8V DC
 9V 2 x 9V DC
 Application : For charging 2 or 4 pcs AA, AAA, C or D size battery (2 batteries per one channel), and 1 to 2 pcs 9V size

Rated Charging Current :

D	C	AA	AAA	9V
560mA	440mA	260mA	120mA	14mA

Charging Time :

Size	Battery Capacity	Charging Time(hours)	Size	Battery Capacity	Charging Time(hours)
AA	1300 mAh	~ 5	D	2200 mAh	~ 5
	1600 mAh	~ 8		4500 mAh	~ 10
	1800 mAh	~ 9		7000 mAh	~ 16
	2000 series	~ 9.5		9000 mAh	~ 21
	2100 series	~ 10			
AAA	2200 series	~ 10.5	C	2200 mAh	~ 5
	2300 series	~ 11		3500 mAh	~ 10
	600 mAh	~ 5		4000 mAh	~ 12
	650 mAh	~ 7		9V	170 mAh
	700 mAh	~ 7.5			
800 mAh	~ 8.5				
850 mAh	~ 9				

MTBF : 30000 hours
 Operating Temperature : 0°C to 45°C
 Storage Temperature : -20°C to 60°C
 Charge Indicator : 2 Green LED for 2 channels; 1 Green LED for 9V
 Dimensions : 178 (L) X 97 (W) X 57 (T)mm
 Approval : Charger - CE
 Adaptor - CE, BS
 Warranty Period : 12 months from ex-factory date.

