



1. INTRODUCTION

A highly volatile, fast drying degreaser designed to remove dust, greases and oils from automotive components.

SAS72 – 500ml Aerosol

2. WHERE TO USE

- On all functional automotive brake components. It may also be used to clean clutch assemblies, including callipers, disc plates etc as well as general degreasing of other metallic components.
- As this product is based solely on a very fast evaporating aliphatic hydrocarbon it is also safe for use on most plastic and rubber components.

3. WHERE NOT TO USE

- On decorative substrates/coatings without first establishing suitability.

4. BENEFITS

- Dissolves and removes brake fluid, grease, oil and dust.
- Cleans brake and clutch parts without the need for dismantling.
- Eliminates brake squeal.
- Powerful spray, fast evaporating formula.
- Eliminates clutch slip caused by contaminated products.

5. PHYSICAL PROPERTIES

Appearance	Clear colourless liquid with a characteristic organic odour.
pH	Not applicable, non-aqueous.
Specific Gravity	0.690 – 0.710
Viscosity	Thin free flowing liquid. Extremely volatile.
Non Volatiles % m/m	Nil.
Active Content % m/m, as supplied	60 – 70
Flammability, as supplied	Extremely flammable, flash point below -20 C
Composition Data, as supplied	A solution of naphtha (petroleum), hydrotreated light in butane/isobutene/propane propellant.
Service Temperature	Designed for use at ambient temperatures.

6. APPLICATION DETAILS

Place a drip tray underneath the work area. Spray liberally onto the surface to be treated and allow contaminated liquid to drain into the tray. Agitation with a brush will assist in the removal of heavy or stubborn contamination. Flush spray until all contamination has been removed and wipe away contaminated cleaner with a soft absorbent cloth. Always test brake operation after cleaning. Always dispose of contaminated materials in a sealable bin to prevent risk of fire.