



**1. INTRODUCTION**

A highly volatile, fast drying solvent based heavy duty degreaser designed to remove dust, greases and oils from automotive components

SAS2 - 500 ml Aerosol

**2. WHERE TO USE**

On all functional components in automotive brake or clutch assemblies, including callipers, discs, clutch plates etc.

**3. WHERE NOT TO USE**

- On decorative substrates, where coatings may be affected
- On plastics or rubber components

**4. BENEFITS**

- Powerful spray, fast evaporating formula
- Cleans Brake and clutch parts without the need for dismantling
- Dissolves and removes brake fluid, grease, oil and dust
- Eliminates brake squeal.
- Eliminates clutch slip caused by contaminated components.

**5. PHYSICAL PROPERTIES**

|                               |  |
|-------------------------------|--|
| Appearance                    | Clear water white aerosol mist with a characteristic organic odour and extremely fast drying properties. |
| pH                            | Not applicable, non-aqueous.   |
| Specific Gravity              | 0.705 – 0.720 [Base Component]   |
| Non Volatiles % m/m           | 0  |
| Active Content % m/m          | 100  |
| Flammability                  | Extremely flammable, flash point below -20°C   |
| Composition Data, descriptive | A blend of low boiling point hydrocarbons, ketone and alcohol solvents propelled by a hydrocarbon blend. |

**6. APPLICATION DETAILS**

Place a drip tray underneath the work area. Shake Well. Hold can upright. Spray liberally onto the surface to be treated, and allow contaminated liquid to drain into the tray. Agitation with a brush will assist in the removal of heavy or stubborn contamination. Flush spray until all contamination has been removed, and wipe away excess with a soft clean cloth. Always work under well ventilated conditions, taking care to avoid vapour inhalation.