



1. INTRODUCTION

A pure silicone based lubricant for general purpose use where slip improvement is required.

SAS8 – 500ml Aerosol

2. WHERE TO USE

For general purpose use on metals, plastics, rubber and most other hard, impervious surfaces.

3. WHERE NOT TO USE

- Where deposition of a high surface slip coating may cause safety problems.
- Silicone O-rings.

4. BENEFITS

- Pure silicone fluid, no other additives.
- Suitable for use on plastics, metals and most rubbers.
- Very high surface slip.
- Fast evaporating carrier solvent.
- Outstanding flow properties.
- Odourless
- Colourless

5. PHYSICAL PROPERTIES (Lubricant base except where stated).

Appearance	Clear water white liquid
pH	Not applicable
Specific Gravity	0.795 +/- 0.010
Viscosity	Slightly viscous liquid
Non Volatiles % m/m	45 - 60
Active Content % m/m, as supplied	5 - 10
Flammability, as supplied	Extremely flammable, flash point below -20°C.
Composition Data, as supplied	A suspension of a silicone polymer in Naphtha (Petroleum) hydrotreated light, in butane, isobutene and propane propellants.
Service Temperature (Continuous)	200 C
Service Temperature (Intermittent)	250 C

6. APPLICATION DETAILS

Shake thoroughly before use. Spray directly onto the component, from a distance of 20 to 30cm, ensuring even coverage. Remove any excess lubricant with a cloth..