



**1. INTRODUCTION**

A silicone free release treatment designed to prevent adhesion of weld spatter residues. This product is water based and provides an environmentally advantageous alternative to solvent based variants.

SAS9 – 500ml Aerosol

**2. WHERE TO USE**

For all general welding operations; on work surfaces, jigs, tools, nozzles etc.

**3. WHERE NOT TO USE**

- No restrictions.

**4. BENEFITS**

- Prevents adhesions
- Excellent non-stick finish.
- Spatter easily removed.
- Not classified a Flammable.
- Water rinseable.

**5. PHYSICAL PROPERTIES (Anti-Spatter base except where stated).**

Appearance	Very pale yellow clear liquid
pH (10% solution)	10 - 11
Specific Gravity	1000 +/- 0.010
Viscosity	Thin liquid
Non Volatiles % m/m	10 - 20
Active Content % m/m, as supplied	90 - 100
Flammability, as supplied	Not classed as flammable
Composition Data, as supplied	An emulsion of refined vegetables oils, alcohol ethoxylate and anionic surfactants and mixed amines in de-ionised water, with nitrogen propellant.
Service Temperature (Continuous)	Not applicable
Service Temperature (Intermittent)	Not applicable

**6. APPLICATION DETAILS**

Shake thoroughly before use. Spray sparingly onto the component, from a distance of 20 to 30cm, ensuring even coverage.