SAFETY DATA SHEET UPHOLSTERY CLEANER VC22

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME UPHOLSTERY CLEANER VC22

PRODUCT NO. 000103068330

SUPPLIER VAN-LINE LTD.

GELDERD ROAD

GELDEKD KI

LEEDS LS12 6NA

0113 213 4300

2 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

CLASSIFICATION Xi;R36. F+;R12. R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	1-5%	R10
ACETONE	200-662-2	67-64-1	5-10%	F;R11 Xi;R36 R66 R67
BUTANE	203-448-7	106-97-8	5-10%	F+;R12
DIETHANOLAMINE	203-868-0	111-42-2	< 1%	Xn;R22,R48/22 Xi;R38,R41
ISOBUTANE	200-857-2	75-28-5	1-5%	F+;R12
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67
PROPANE	200-827-9	74-98-6	1-5%	F+;R12
SODIUM NITRITE	231-555-9	7632-00-0	< 1%	O;R8 T;R25 N;R50
TURPENTINE, OIL	232-350-7	8006-64-2	< 1%	R10 Xn;R20/21/22,R65 R43 Xi;R36/38 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
DIETHANOLAMINE	OES	3 ppm	13 mg/m3		
ISOBUTANE	WEL	800 ppm		800 ppm	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating
TURPENTINE, OIL	WEL	100 ppm	566 mg/m3	150 ppm	850 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. Use chemical cartridge protection with appropriate cartridge.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol COLOUR White

ODOUR Characteristic SOLUBILITY Soluble in water

FLAMMABILITY LIMIT - LOWER(%) 0.8

FLAMMABILITY LIMIT - UPPER(%) 13.

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

SKIN CONTACT

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes. May cause chemical eye burns.

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

FCOTOXICITY

Dangerous for the environment if discharged into watercourses.

DEGRADABILITY

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



	_
UK ROAD CLASS	2

PROPER SHIPPING NAME **AEROSOLS**

UN NO. ROAD 1950 UK ROAD PACK GR. N/A

ADR CLASS NO. 2 ADR CLASS Class 2: Gases

ADR PACK GROUP ADR LABEL NO. N/A 2.1 RID CLASS NO. 2 **RID PACK GROUP** N/A UN NO. SEA **IMDG CLASS** 1950 21 IMDG PACK GR. Not Applicable **EMS** F-D, S-U MARINE POLLUTANT No. UN NO. AIR 1950

IMDG SUB CLASS

AIR CLASS

6.1

2.1

AIR PACK GR.

N/A

15 REGULATORY INFORMATION

LABELLING





Irritant Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2 Keep out of the reach of children

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S51 Use only in well-ventilated areas.

DETERGENT LABELLING

< 5% Perfumes

Anionic surfactants

Contains NATRIUMNITRIET, CITRAL, d-LIMONENE, SODIUM BENZOATE

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 27/05/2008

REV. NO./REPL. SDS GENERATED 10

RISK PHRASES IN FULL

R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R22 Harmful if swallowed.
 R25 Toxic if swallowed.
 R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50 Very toxic to aquatic organisms.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.
R8 Contact with combustible material may cause fire.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.