SAFETY DATA SHEET

UNIVERSAL CLEANER

Issued: 17.04.2008

Revision No: 3

Page 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UNIVERSAL CLEANER

Company name: VAN-LINE LTD.

GELDERD ROAD

LEEDS

LS12 6NA

T - 0113 213 4300

F - 0113 213 4319

Email: contact@van-line.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DISODIUM METASILICATE 1-5%

EINECS: 229-912-9 CAS: 6834-92-0

[C] R34; [Xi] R37

• 2-(2-BUTOXYETHOXY)ETHANOL 1-5%

EINECS: 203-961-6 CAS: 112-34-5

[Xi] R36

• 2-BUTOXYETHANOL 1-5%

EINECS: 203-905-0 CAS: 111-76-2

[Xn] R20/21/22; [Xi] R36/38

• PRIMARY ALCOHOL ETHOXYLATE 1-5%

CAS: 68439-45-2

[Xn] R22; [Xi] R41

• 02845000 1-5%

CAS: 1300-72-7

[Xi] R36

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Issued: 17.04.2008

SAFETY DATA SHEET

UNIVERSAL CLEANER

Page 2

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn

leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: 2-(2-BUTOXYETHOXY)ETHANOL

WEL (8 hr TWA): 100 mg/m3 WEL (15 min STEL): 100 mg/m3

• 2-BUTOXYETHANOL

WEL (8 hr TWA): 25 ppm WEL (15 min STEL): 50 ppm

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Blue

Issued: 17.04.2008

SAFETY DATA SHEET

UNIVERSAL CLEANER

Page 3

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Non-viscous

Flash point°C: >70

pH: >12

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: DISODIUM METASILICATE

ORL MUS LD50 770 mg/kg

ORL RAT LD50 1153 mg/kg

• 2-(2-BUTOXYETHOXY)ETHANOL

ORL MUS LD50 6050 mg/kg

ORL RAT LD50 4500 mg/kg

2-BUTOXYETHANOL

IVN RAT LD50 307 mg/kg

ORL MUS LD50 1230 mg/kg

ORL RAT LD50 470 mg/kg

• PRIMARY ALCOHOL ETHOXYLATE

ORL RAT LD50 >200<2000 mg/kg

• 02845000

ORL RAT LD50 >7000 mg/kg

Chronic toxicity: May cause sensitisation by skin contact.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Hazardous ingredients: PRIMARY ALCOHOL ETHOXYLATE

FISH 96H LC50 1-10 mg/l

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

Issued: 17.04.2008

SAFETY DATA SHEET

UNIVERSAL CLEANER

Page 4

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1760 ADR Class: 8

Packing group: III Classification code: C9

Shipping name: CORROSIVE LIQUID, N.O.S. (DISODIUM METASILICATE)

Labelling: 8 Hazard ID no: 80



IMDG / IMO

UN no: 1760 Class: 8

Packing group: III EmS: 8-15

Marine pollutant: .

Labelling: 8

IATA / ICAO

UN no: 1760 Class: 8

Packing group: III

Packing instructions: 818(P&CA); 820(PAO)

Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

SAFETY DATA SHEET

UNIVERSAL CLEANER

Page 5

16. OTHER INFORMATION

Risk phrases used in s.3: R34: Causes burns.

R37: Irritating to respiratory system.

R36: Irritating to eyes.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R36/38: Irritating to eyes and skin.

R22: Harmful if swallowed.

R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.